


EARTHMAX SR 22

| | |
|---------------------|--|
| TIRE SIZE | 17.5 R 25 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PLANIERER / RADLADER / PLANIERER / RADLADER / PLANIERER / PLANIERER |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 167 B ; 182 A2 |



ABMESSUNGEN IS STANDARD

| | | | |
|-----------------|-----------|--------------------|-------|
| OD (MM) | 1350 | TRA CODE | E2/L2 |
| SLR (MM) | 590 | STAR RATING | ★★ |
| RC (MM) | 3950 | | |
| RIM REC | 14.00/1.5 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 |
|------------|------|------|------|------|------|------|------|------|------|------|------|
| 50 | 4375 | 4625 | 4750 | 5000 | 5150 | 5450 | -- | -- | -- | -- | -- |
| 10 | -- | -- | -- | -- | -- | 7300 | 7500 | 7750 | 8000 | 8250 | 8500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.