


AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 15.0/55 - 17 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 122 A8 |
| LI/SS FREE ROLLING | 134 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 380 | RIM REC | 13.00 |
| OD (MM) | 890 | RIM ALT | 13 |
| SLR (MM) | 395 | ECE | E4-106R-001571 |
| RC (MM) | 2608 | PR | 10 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.60 |
|-------------------|-------------|
| 10 FR | 2970 |
| 25 FR | 2525 |
| 30 FR | 2375 |
| 40 FR | 2120 |
| 10 DW | 2100 |
| 25 DW | 1785 |
| 30 DW | 1680 |
| 40 DW | 1500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.