

# XL GRIP (L3)

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 17.5 - 25                                |
| <b>UM</b>           | US STANDARD                              |
| <b>CONSTRUCTION</b> | ⊠ BIAS                                   |
| <b>MACHINERY</b>    | HJULLASTARE / HJULLASTARE /<br>BULLDOZER |
| <b>VERSION</b>      | DUAL BEAD                                |
| <b>TIRE TYPE</b>    | TL                                       |



## DIMENSIONER US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>USA CODE</b> | 94063406 | <b>RIM REC</b>  | 14.00/1.5 |
| <b>OD (IN)</b>  | 53.0     | <b>PR</b>       | 24        |
| <b>SLR (IN)</b> | 24.5     | <b>TRA CODE</b> | E3/L3     |
| <b>RC (IN)</b>  | 156.7    |                 |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 84    | 102   |
|-----------|-------|-------|
| 30        | 13550 | -     |
| 5         | -     | 22000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.