

# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>480/65 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	140 D ; 143 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	W 15 L
<b>OD (MM)</b>	1234	<b>RIM ALT</b>	W 14 L
<b>SLR (MM)</b>	562	<b>ECE</b>	E4-106R-000617
<b>RC (MM)</b>	3730	<b>SRI</b>	600

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	1200	1400	1575	1750	1925	2075	2300	2500
<b>50</b>	1260	1470	1655	1840	2025	2180	2415	2625
<b>40</b>	1310	1530	1720	1910	2100	2265	2510	2725
<b>30</b>	1380	1610	1815	2015	2215	2390	2645	2875
<b>10 LT</b>	1610	1880	2115	2345	2580	2785	3085	3350
<b>10 HT</b>	1380	1610	1815	2015	2215	2390	2645	2875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.