


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 710/70 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	185 D



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94066148	<b>RC (IN)</b>	243.4
<b>SW (IN)</b>	28.1	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	81.1	<b>RIM ALT</b>	DW 23 B; DW 24 B
<b>SLR (IN)</b>	36.3	<b>ECE</b>	E11-106R-0010959

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	8730	10020	11510	13000	14470	15960	17450	18550
<b>FROM 40 TO 25</b>	9590	11010	12640	14270	15910	17540	19170	20390
20	9780	11230	12900	14560	16230	17890	19550	20800
12	9980	11450	13150	14850	16540	18240	19940	21210
5	10550	12110	13910	15710	17500	19300	21090	22430
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	13430	15420	17700	19980	22280	24560	26840	28550
5 HT	9780	11230	12900	14560	16230	17890	19550	20800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.