


# EARTHMAX SR 35

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 775/65 R 29  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | RADLADER / RADLADER / RADLADER   |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 213 A2   |



## ABMESSUNGEN IS STANDARD

|                 |           |                    |                      |
|-----------------|-----------|--------------------|----------------------|
| <b>OD (MM)</b>  | 1752      | <b>RIM ALT</b>     | 24.00/3.0; 25.00/3.5 |
| <b>SLR (MM)</b> | 787       | <b>TRA CODE</b>    | L3                   |
| <b>RC (MM)</b>  | 5311      | <b>STAR RATING</b> | ★★                   |
| <b>RIM REC</b>  | 24.00/3.5 |                    |                      |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.00  | 5.25  | 5.50  | 5.75  | 6.00  | 6.25  |
|------------|-------|-------|-------|-------|-------|-------|
| 10         | 17500 | 18500 | 19000 | 19500 | 20000 | 20600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.