

# AS 504

<b>TIRE SIZE</b>	7.5L - 15
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	100 A8
<b>LI/SS FREE ROLLING</b>	113 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	210	<b>RIM REC</b>	6 LB
<b>OD (MM)</b>	765	<b>RIM ALT</b>	5 K; 5½ J; 5½ K
<b>SLR (MM)</b>	354	<b>ECE</b>	E11-106R-004240
<b>RC (MM)</b>	2280	<b>PR</b>	8

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.70
10 FR	1610
25 FR	1370
30 FR	1290
40 FR	1150
10 DW	1120
25 DW	950
30 DW	895
40 DW	800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.