

## SM 55 L5S

|                  |                                                                    |
|------------------|--------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>17.5 - 25</b>                                                   |
| <b>UM</b>        | US STANDARD                                                        |
| <b>MACHINERY</b> | VEHÍCULOS PARA MINERÍA<br>SUBTERRÁNEA / VOLQUETE DE PERFIL<br>BAJO |
| <b>VERSIÓN</b>   | STEEL BELTED                                                       |
| <b>TIRE TYPE</b> | TL                                                                 |



### DIMENSIONES US STANDARD

|                   |          |                 |                            |
|-------------------|----------|-----------------|----------------------------|
| <b>CÓDIGO USA</b> | 94040216 | <b>RIM REC</b>  | 14.00/1.5                  |
| <b>OD (IN)</b>    | 54.1     | <b>RIM ALT</b>  | 14.00/1.3 ; 14.00/1.4 (DC) |
| <b>SLR (IN)</b>   | 24.8     | <b>PR</b>       | 20                         |
| <b>RC (IN)</b>    | 159.2    | <b>TRA CODE</b> | L5S                        |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 83    |
|-----------|-------|
| 5         | 18200 |
| 10        | 15800 |
| 15        | 14600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.