

# EARTHMAX SR 30

|           |                                                  |
|-----------|--------------------------------------------------|
| TIRE SIZE | 15.5 R 25                                        |
| UM        | IS STANDARD                                      |
| MACHINERY | ARTICULATED DUMP TRUCK (ADT) /<br>DOZER / LOADER |
| VERSION   | CUT RESISTANT COMPOUND                           |
| TL/TT     | TL                                               |
| LI/SS     | 160 B ; 169 A2                                   |



## DIMENSIONS IS STANDARD

|          |           |             |       |
|----------|-----------|-------------|-------|
| OD (MM)  | 1276      | RIM ALT     | -     |
| SLR (MM) | 574       | TRA CODE    | E3/L3 |
| RC (MM)  | 3809      | STAR RATING | ★★/★  |
| RIM REC  | 12.00/1.3 |             |       |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 |
|------------|------|------|------|------|------|------|
| 50         | 3650 | 3875 | 4000 | 4250 | 4375 | 4500 |
| 10         | 5000 | 5150 | 5450 | 5600 | 5800 | -    |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.