

AGRIMAX V-FLECTO

TYRE SIZE	VF 380/85 R 34
UM	IS STANDARD
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	160 E



DIMENSIONS IS STANDARD

SW (MM)	390	RIM REC	W 13
OD (MM)	1510	RIM ALT	W 11
SLR (MM)	680	ECE	E11-106R-0012141
RC (MM)	4511	SRI	625

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
70	1755	2070	2385	2655	2970	3240	3555	3825	4185	4500
FROM 65 TO 40	1755	2070	2385	2655	2970	3240	3555	3825	4185	4500
30	1795	2115	2435	2710	3030	3305	3630	3905	4270	4590
20	1830	2155	2485	2765	3090	3370	3700	3980	4355	4680
10	1935	2280	2625	2925	3270	3565	3915	4210	4605	4950
*UPTO 10 CYC WITH FRONT LOADER	2610	3080	3545	3945	4415	4815	5285	5685	6220	6685
10HT	1795	2115	2435	2710	3030	3305	3630	3905	4270	4590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.