

FLOTATION 648

TIRE SIZE	600/55 - 22.5
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI
VERSIONE	DUAL BEAD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	160 A8/156 B
LI/SS FREE ROLLING	173 A8/169 B



DIMENSIONI IS STANDARD

SW (MM)	600	RIM REC	AG 20.00
OD (MM)	1230	ECE	E11-106R-004393
SLR (MM)	540	PR	20
RC (MM)	3716		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.00	3.10	3.20
10 FR	8765	8930	9100
20 FR	7890	8040	8190
30 FR	7010	7145	7280
40 FR	6260	6380	6500
50 FR	5635	5740	5800
10 DW	6070	6180	6300
20 DW	5460	5565	5670
30 DW	4855	4945	5040
40 DW	4335	4415	4500
50 DW	3900	3975	4000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.