

AGRIMAX RT 855

TIRE SIZE	420/80 R 46
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN / ARBETSFORDON
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	159 D ; 170 A2



DIMENSIONER IS STANDARD

SW (MM)	418	RIM REC	W 13
OD (MM)	1840	RIM ALT	W 12
SLR (MM)	863	ECE	E4-106R-001489
RC (MM)	5641	SRI	900

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
65	1625	1865	2140	2415	2695	2970	3210	3450	4070	4375
50	1705	1960	2250	2540	2830	3120	3375	3625	4275	4595
40	1780	2045	2345	2650	2950	3255	3520	3780	4460	4795
30	1870	2145	2465	2780	3100	3415	3695	3970	4685	5035
10	2235	2565	2945	3325	3705	4085	4420	4750	5580	6000
10 LT	2175	2500	2870	3240	3610	3980	4305	4625	5455	5865
10 HT	1870	2145	2465	2780	3100	3415	3695	3970	4685	5035

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.