

# BK 826

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>8.25 - 16</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | TRAILER / IMPLEMENTS / HARVESTER<br>/ TRAILER / BACKHOE LOADER |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94034475 | <b>RIM ALT</b> | 6.00 G         |
| <b>SW (IN)</b>  | 9.4      | <b>ECE</b>     | E4-54R-0024097 |
| <b>OD (IN)</b>  | 34.0     | <b>PR</b>      | 18             |
| <b>RIM REC</b>  | 6.50 H   |                |                |

## LOAD CAPACITY (LBS/TIRE)

|                  |            |
|------------------|------------|
| <b>MPH / PSI</b> | <b>115</b> |
| <b>62 LS</b>     | 4190       |
| <b>62 LD</b>     | 3970       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.