


# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>650/65 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN / SPRIDARE / TRAKTOR / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	157 D ; 160 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94053667	<b>RC (IN)</b>	214.3
<b>SW (IN)</b>	25.4	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	71.3	<b>ECE</b>	E11-106R-002990
<b>SLR (IN)</b>	32.8		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	5090	6010	6820	7640	8370	9090
30	5360	6320	7180	8040	8800	9560
25	5560	6550	7440	8330	9130	9920
20	5860	6910	7850	8800	9630	10460
5 LT	6830	8050	9150	10250	11220	12190
5 HT	5860	6910	7850	8800	9630	10460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.