

AGRIMAX RT 657

TIRE SIZE	600/65 R 34
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	157 D ; 160 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	611	RIM REC	DW 20 B
OD (MM)	1644	RIM ALT	W 18 L
SLR (MM)	742	ECE	E4-106R-001405
RC (MM)	4960	SRI	775

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1980	2310	2600	2890	3180	3425	3795	4125
50	2085	2430	2735	3035	3340	3600	3990	4335
40	2160	2520	2835	3150	3465	3735	4140	4500
30	2280	2660	2990	3325	3655	3940	4370	4745
10 LT	2655	3100	3485	3875	4260	4590	5090	5530
10 HT	2280	2660	2990	3325	3655	3940	4370	4745

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.