



IS standard



GROWING TOGETHER

DON 2000



PRODUCT DATA SHEET



Bias

Performance



Durability



On/Off Road



DON 2000

DON 2000 is a suitable for transport operations with trailers and light trucks both on and off the road. It ensures extra durability along with high performance during the entire product life-cycle.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16"	7.50 - 16	6.00 G	5.50 F	216	840	-	-	STD	16	TT	-
Ø 20"	9.00 - 20	7.0	6.5 ; 7.5	270	1048	-	-	STD	16	TT	-
	9.00 - 20	7.0	6.5 ; 7.5	270	1048	-	-	TR TR	16	TT	-
	10.00 - 20	7.5	7.0 ; 8.0	286	1080	-	-	IND TR	16	TT	-
	10.00 - 20	7.5	7.0 ; 8.0	286	1080	-	-	IND TR	18	TT	-
	11.00 - 20	8.0	7.5 ; 8.5	292	1110	520	3414	STD	18	TT	-
	12.00 - 20	8.5	8.0 ; 9.0	315	1145	535	3519	STD	18	TT	-
Ø 24"	12.00 - 24	8.5	8.0 ; 9.0	315	1245	-	-	STD	18	TT	-

STD: Standard - TR TR: Tractor Trailer - IND TR: Industrial Trailer



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference