


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>480/80 R 50</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	159 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	489	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	2036	<b>RIM ALT</b>	DW 15 L ; W 15 L
<b>SLR (MM)</b>	941	<b>ECE</b>	E4-106R-001486
<b>RC (MM)</b>	6183	<b>SRI</b>	975

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	2060	2365	2715	3065	3415	3765	4070	4375
40	2060	2365	2715	3065	3415	3765	4070	4375
30	2205	2530	2905	3280	3655	4030	4360	4685
10 LT	2760	3170	3640	4110	4575	5045	5455	5865
10 HT	2205	2530	2905	3280	3655	4030	4360	4685

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.