


AGRIMAX RT 657

| | |
|---------------------|--|
| TYRE SIZE | 540/65 R 34 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 152 D ; 155 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94028412 | RC (IN) | 186.7 |
| SW (IN) | 20.9 | RIM REC | W 16 L |
| OD (IN) | 61.7 | RIM ALT | W 18 L |
| SLR (IN) | 28.0 | ECE | E4-106R-000652 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|------|------|------|-------|
| 40 | 3760 | 4390 | 4940 | 5480 | 6030 | 6500 | 7210 | 7850 |
| 30 | 3960 | 4610 | 5180 | 5760 | 6340 | 6830 | 7570 | 8220 |
| 25 | 4100 | 4780 | 5390 | 5990 | 6580 | 7100 | 7860 | 8540 |
| 20 | 4330 | 5050 | 5680 | 6300 | 6940 | 7480 | 8290 | 9010 |
| 5 LT | 5040 | 5890 | 6610 | 7350 | 8090 | 8720 | 9660 | 10490 |
| 5 HT | 4330 | 5050 | 5680 | 6300 | 6940 | 7480 | 8290 | 9010 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.