

AGRIMAX RT 955

TIRE SIZE	210/95 R 32
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	120 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94040018	RC (IN)	145.8
SW (IN)	8.4	RIM REC	W 7
OD (IN)	47.8	RIM ALT	W 6
SLR (IN)	22.5	ECE	E4-106R-001391

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52
30	1420	1830	2230	2410	2620	2880	3090	-
25	1420	1830	2230	2410	2620	2880	3090	-
20	1520	1950	2380	2580	2810	3080	3310	-
5	2000	2600	3150	3430	3660	4030	4350	4630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.