

# AW 702

<b>TIRE SIZE</b>	<b>13.0/55 - 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	▣ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	133 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	336	<b>RIM REC</b>	11.0
<b>OD (MM)</b>	770	<b>ECE</b>	E4-106R-002751
<b>SLR (MM)</b>	345	<b>PR</b>	14
<b>RC (MM)</b>	2256		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.20
10 FR	2885
25 FR	2450
30 FR	2305
40 FR	2060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.