

# FL 630 SUPER

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>750/60 R 30.5</b>                     |
| <b>UM</b>           | US STANDARD                              |
| <b>CONSTRUCTION</b> |  |
| <b>MACHINERY</b>    | SPREADER / TANKER / TRAILER / IMPLEMENTS |
| <b>VERSION</b>      | STANDARD                                 |
| <b>TIRE TYPE</b>    | TL                                       |
| <b>LI/SS</b>        | 181 D                                    |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94041190 | <b>RC (IN)</b> | 201.4          |
| <b>SW (IN)</b>  | 29.7     | <b>RIM REC</b> | AG 24.00       |
| <b>OD (IN)</b>  | 65.9     | <b>ECE</b>     | E4-106R-001499 |
| <b>SLR (IN)</b> | 29.4     |                |                |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12    | 15    | 17    | 23    | 29    | 35    | 41    | 46    | 52    | 58    |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45        | 5300  | 6130  | 6960  | 8450  | 9780  | 11260 | 12750 | 13750 | 15230 | 16560 |
| 40        | 5820  | 6730  | 7640  | 9280  | 10740 | 12370 | 14010 | 15100 | 16730 | 18190 |
| 30        | 7050  | 8160  | 9250  | 11230 | 13000 | 14970 | 16970 | 18280 | 20260 | 22010 |
| 25        | 7930  | 9160  | 10390 | 12620 | 14590 | 16820 | 19050 | 20530 | 22760 | 24730 |
| 15        | 9200  | 10640 | 12070 | 14660 | 16960 | 19540 | 22130 | 23850 | 26440 | 28740 |
| 5         | 10480 | 12120 | 13760 | 16700 | 19320 | 22270 | 25210 | 27180 | 30120 | 32740 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.