


EARTHMAX SR 53

| | |
|---------------------|--|
| TIRE SIZE | 29.5 R 29 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BULDOZER / ÎNCĂRCĂTOR / AUTOBASCULANTĂ CU PROFIL REDUS (LPDT) |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 223 A2 |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|--------------------|-----------|
| USA CODE | 94069590 | RIM REC | 25.00/3.5 |
| OD (IN) | 79.3 | RIM ALT | 24.00/3.5 |
| SLR (IN) | 35.6 | TRA CODE | L5 |
| RC (IN) | 238.5 | STAR RATING | ★★★ |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 98 | 102 | 105 | 109 | 112 | 116 |
|-----------|-------|-------|-------|-------|-------|-------|
| 5 | 53600 | 55100 | 56800 | 57800 | 58900 | 60000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.