


AGRIMAX V-FLECTO



| | |
|---------------------|--|
| TIRE SIZE | VF 650/60 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRATTORE A ELEVATA POTENZA / TRATTORE |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 173 D |

DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CODICE USA | 94065370 | RC (IN) | 205.4 |
| SW (IN) | 25.6 | RIM REC | DW 23 B |
| OD (IN) | 68.7 | RIM ALT | DW 21 B |
| SLR (IN) | 30.5 | ECE | E11-106R-006415 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|--------------------------------------|------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 6010 | 6910 | 7960 | 8870 | 9920 | 10820 | 12140 | 13040 |
| FROM 40 TO 25 | 6590 | 7590 | 8740 | 9740 | 10890 | 11890 | 13330 | 14330 |
| 20 | 6720 | 7750 | 8920 | 9940 | 11110 | 12140 | 13600 | 14620 |
| 12 | 6860 | 7900 | 9090 | 10140 | 11330 | 12380 | 13870 | 14900 |
| 5 | 7250 | 8360 | 9620 | 10720 | 11980 | 13080 | 14660 | 15760 |
| *UPTO 5 CYC WITH FRONT LOADER | 9240 | 10640 | 12250 | 13650 | 15260 | 16650 | 18660 | 20060 |
| 5 HT | 6720 | 7750 | 8920 | 9940 | 11110 | 12140 | 13600 | 14620 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.