


# AS 504

<b>TIRE SIZE</b>	<b>7.50 - 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	LEVANTADOR TELESCÓPICO / REBOQUE PARA OS CAMPOS / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	111 A8
<b>LI/SS FREE ROLLING</b>	122 A8



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	209	<b>RIM REC</b>	5.50 F
<b>OD (MM)</b>	854	<b>RIM ALT</b>	4.50 E; 6.00 F; 5.00 F
<b>SLR (MM)</b>	407	<b>ECE</b>	E11-106R-006456
<b>RC (MM)</b>	2649	<b>PR</b>	12

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>5.10</b>
10 FR	2100
25 FR	1785
30 FR	1680
40 FR	1500
10 DW	1525
25 DW	1295
30 DW	1220
40 DW	1090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.