


# AW 711

<b>TIRE SIZE</b>	<b>IF 340/65 R 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STUBBLE RESISTANT
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	153 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94053476	<b>RC (IN)</b>	106.4
<b>SW (IN)</b>	13.0	<b>RIM REC</b>	W 11
<b>OD (IN)</b>	35.4	<b>ECE</b>	E11-106R-002992
<b>SLR (IN)</b>	15.0		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58
<b>FROM 5 TO 30 MPH</b>	2580	3380	4110	4750	5480	6210	6680	7330	8050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.