


AW 711

TIRE SIZE	395/55 R 16.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ERNTMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / ERNTMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STUBBLE RESISTANT
TIRE TYPE	TL
LI/SS	152 A8/B



ABMESSUNGEN IS STANDARD

SW (MM)	394	RIM REC	12
OD (MM)	838	ECE	E11-106R-002997
SLR (MM)	365	SRI	400
RC (MM)	2516		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
50	1065	1385	1705	1955	2275	2595	2770	3055	3340	3550
40	1065	1385	1705	1955	2275	2595	2770	3055	3340	3550
30	1195	1555	1915	2190	2550	2910	3105	3425	3745	3980
25	1270	1650	2030	2325	2705	3085	3300	3635	3975	4225
20	1345	1750	2150	2465	2865	3270	3495	3850	4210	4475
10	1495	1940	2390	2735	3185	3630	3880	4275	4675	4970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.