DATA SHEET

PRINTED ON
23-04-2026

AS 504

TIRE SIZE	**7.50 - 18**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
VERSIÓN	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	101 A8
LI/SS FREE ROLLING	114 A8

DIMENSIONES IS STANDARD

SW (MM)	209	**RIM REC**	5.50 F
OD (MM)	854	**RIM ALT**	4.50 E; 6.00 F; 5.00 F
SLR (MM)	407	**ECE**	E4-106R-002638
RC (MM)	2649	**PR**	8

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.10
10 FR	1650
25 FR	1405
30 FR	1320
40 FR	1180
10 DW	1155
25 DW	980
30 DW	925
40 DW	825

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..