

# TR 387

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 23.1 - 26                                       |
| <b>UM</b>           | IS STANDARD                                     |
| <b>CONSTRUCTION</b> | BIAS  |
| <b>MACHINERY</b>    | REMOLQUE / MAQUINARIA AGRÍCOLA<br>/ COMPACTADOR |
| <b>VERSIÓN</b>      | DUAL BEAD                                       |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 159 A6  |



## DIMENSIONES IS STANDARD

|                 |      |                 |         |
|-----------------|------|-----------------|---------|
| <b>SW (MM)</b>  | 592  | <b>RIM REC</b>  | DW 20 B |
| <b>OD (MM)</b>  | 1560 | <b>PR</b>       | 16      |
| <b>SLR (MM)</b> | 690  | <b>SRI</b>      | 750     |
| <b>RC (MM)</b>  | 4688 | <b>TRA CODE</b> | R3      |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.30</b> |
| 30                | 4375        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.