


AGRIMAX V-FLECTO



| | |
|---------------------|--|
| TIRE SIZE | VF 710/70 R 42 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTEUR DE FORTE PUISSANCE / TRACTEUR |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 185 D |

DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| CODE USA | 94075812 | RC (IN) | 243.4 |
| SW (IN) | 28.1 | RIM REC | DW 25 B |
| OD (IN) | 81.1 | RIM ALT | DW 23 B; DW 24 B |
| SLR (IN) | 35.8 | ECE | E11-106R-006266 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 8730 | 10020 | 11510 | 13000 | 14470 | 15960 | 17450 | 18550 |
| FROM 40 TO 25 | 9590 | 11010 | 12640 | 14270 | 15910 | 17540 | 19170 | 20390 |
| 20 | 9780 | 11230 | 12900 | 14560 | 16230 | 17890 | 19550 | 20800 |
| 12 | 9980 | 11450 | 13150 | 14850 | 16540 | 18240 | 19940 | 21210 |
| 5 | 10550 | 12110 | 13910 | 15710 | 17500 | 19300 | 21090 | 22430 |
| UPTO 20 CYC | 10880 | 12500 | 14350 | 16200 | 18050 | 19910 | 21760 | 23140 |
| UPTO 10 CYC | 12980 | 14920 | 17130 | 19340 | 21550 | 23760 | 25970 | 27620 |
| UPTO 5CYC | 14240 | 16360 | 18780 | 21200 | 23620 | 26050 | 28470 | 30280 |
| 5 HT | 9780 | 11230 | 12900 | 14560 | 16230 | 17890 | 19550 | 20800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.