

# AGRIMAX RT 765

|                  |                                                                                 |
|------------------|---------------------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>480/70 R 30</b>                                                              |
| <b>UM</b>        | US STANDARD                                                                     |
| <b>MACHINERY</b> | PULVERIZADOR / TRACTOR /<br>VENDIMIADORA / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| <b>VERSIÓN</b>   | SPECIAL                                                                         |
| <b>TIRE TYPE</b> | TL                                                                              |
| <b>LI/SS</b>     | 141 D                                                                           |

## DIMENSIONES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94062294 | <b>RC (IN)</b> | 172.1           |
| <b>SW (IN)</b>    | 18.9     | <b>RIM REC</b> | W 15 L          |
| <b>OD (IN)</b>    | 58.2     | <b>RIM ALT</b> | W 14 L ; W 16 L |
| <b>SLR (IN)</b>   | 25.9     | <b>ECE</b>     | E11-106R-005522 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>40</b>   | 3130 | 3640 | 4140 | 4660 | 5170 | 5680 |
| <b>30</b>   | 3280 | 3820 | 4350 | 4890 | 5430 | 5960 |
| <b>25</b>   | 3430 | 3980 | 4540 | 5100 | 5670 | 6220 |
| <b>20</b>   | 3600 | 4190 | 4770 | 5370 | 5950 | 6540 |
| <b>5 LT</b> | 4200 | 4880 | 5570 | 6250 | 6930 | 7620 |
| <b>5 HT</b> | 3600 | 4190 | 4770 | 5370 | 5950 | 6540 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

