


AW 711

| | |
|---------------------|--|
| TIRE SIZE | 340/60 R 16.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MIETITREBBIA / ATTREZZI AGRICOLI / MIETITREBBIA / ATTREZZI AGRICOLI |
| VERSIONE | STUBBLE RESISTANT |
| TIRE TYPE | TL |
| LI/SS | 145 A8/B |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CODICE USA | 94044788 | RC (IN) | 97.5 |
| SW (IN) | 12.8 | RIM REC | 11 |
| OD (IN) | 32.3 | ECE | E4-106R-001392 |
| SLR (IN) | 14.5 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 73 |
|-----------|------|------|------|------|------|------|------|------|------|------|
| 30 | 1920 | 2500 | 3080 | 3520 | 4100 | 4670 | 4990 | 5500 | 6020 | 6390 |
| 25 | 1920 | 2500 | 3080 | 3520 | 4100 | 4670 | 4990 | 5500 | 6020 | 6390 |
| 20 | 2150 | 2800 | 3440 | 3950 | 4590 | 5240 | 5590 | 6160 | 6730 | 7160 |
| 15 | 2290 | 2980 | 3660 | 4200 | 4880 | 5570 | 5940 | 6560 | 7160 | 7620 |
| 10 | 2420 | 3150 | 3870 | 4440 | 5160 | 5890 | 6290 | 6930 | 7580 | 8060 |
| 5 | 2690 | 3490 | 4300 | 4930 | 5730 | 6540 | 6990 | 7700 | 8420 | 8950 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.