



AW 726

Description

AW 726 has been specially designed for trailers in transport operations. It is best suited for both on-and-off-the-road usage. AW 726 shows excellent road performance and self-cleaning features. The block pattern design provides an extended tyre life-cycle.

UM

US Standard

Construction

▣ Bias

Machinery

Agriculture ■ Trailer



Version

STEEL BELTED

Tyre Type

TL

Tyre size

11.5/80-15.3

LI/SS

Dimensions US Standard

USA Code	94067695
SW (in)	11.8
OD (in)	33.7
SLR (in)	14.7
RC (in)	100.0
Rim Rec	9.00
ECE	E11-106R-006974

Load Capacity (US)

mph / psi	70
5 FR	7500
15 FR	6370
20 FR	6000
25 FR	5360
5 DW	5250
15 DW	4460
20 DW	4200
25 DW	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..