

FLOTATION 648

| | |
|---------------------------|----------------------------------------------------------------------------------------------|
| TIRE SIZE | 850/50 - 30.5 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION | HD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 174 A8/170 B |
| LI/SS FREE ROLLING | 186 A8/182 B |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA-CODE | 94030156 | RC (IN) | 194.3 |
| SW (IN) | 33.5 | RIM REC | AG 28.00 |
| OD (IN) | 65.0 | ECE | E11-106R-004565 |
| SLR (IN) | 28.0 | PR | 16 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 26 | 29 | 32 |
|--------------|-------|-------|-------|
| 5 FR | 26080 | 27730 | 29320 |
| 10 FR | 23470 | 24950 | 26390 |
| 20 FR | 20870 | 22190 | 23460 |
| 25 FR | 18630 | 19810 | 20940 |
| 30 FR | 16770 | 17820 | 18740 |
| 5 DW | 18400 | 19550 | 20680 |
| 10 DW | 16560 | 17590 | 18610 |
| 20 DW | 14720 | 15640 | 16540 |
| 25 DW | 13140 | 13970 | 14770 |
| 30 DW | 11830 | 12570 | 13230 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.