

# PL 801

<b>TIRE SIZE</b>	7.00 - 15
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	РОТОРНЫЕ ГРАБЛИ / СЕНОВОРОШИЛКА / КОМБАЙН / ВИЛОЧНЫЙ ПОГРУЗЧИК / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ВИЛОЧНЫЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94007233	<b>RIM ALT</b>	4.33 R; 5.0
<b>SW (IN)</b>	7.9	<b>PR</b>	12
<b>OD (IN)</b>	29.5		
<b>RIM REC</b>	5.5		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	120
15 LOAD WHEEL	6770
15 STEER WHEEL	5205
5 OTHER VEHICLES	6770
15 OTHER VEHICLES	5205
STATIC SIDE LOADER	7860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.