

# CON STAR

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>400/70 - 20</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS                       |
| <b>MACHINERY</b>    | КОМПАКТНЫЙ ПОГРУЗЧИК /<br>ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК<br>/ КОМПАКТНЫЙ ПОГРУЗЧИК /<br>ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК |
| <b>VERSION</b>      | INDUSTRIAL   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 149 A8   |



## РАЗМЕРЫ IS STANDARD

|                 |      |                |                    |
|-----------------|------|----------------|--------------------|
| <b>SW (MM)</b>  | 405  | <b>RIM REC</b> | 13                 |
| <b>OD (MM)</b>  | 1080 | <b>RIM ALT</b> | 12 SDC; 13 SDC; 14 |
| <b>SLR (MM)</b> | 501  | <b>ECE</b>     | E11-106R-003024    |
| <b>RC (MM)</b>  | 3303 | <b>PR</b>      | 16                 |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.00</b> |
| 40                | 3250        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.