


# AGRIMAX FORCE



<b>TIRE SIZE</b>	<b>IF 600/70 R 30</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН / ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	165 D

## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	603	<b>RIM REC</b>	DW 21 B; DW 21 A
<b>OD (MM)</b>	1602	<b>RIM ALT</b>	DW 20 A; DW 20 B
<b>SLR (MM)</b>	708	<b>ECE</b>	E11-106R-006495
<b>RC (MM)</b>	4800	<b>SRI</b>	750

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2200	2525	2900	3280	3650	4025	4400	4685
<b>FROM 65 TO 40</b>	2420	2780	3190	3605	4015	4425	4840	5150
30	2515	2890	3315	3745	4175	4600	5030	5355
20	2610	3000	3445	3890	4335	4775	5225	5560
10	3070	3530	4050	4575	5095	5615	6145	6540
<b>UPTO 30 CYC</b>	3145	3610	4145	4685	5215	5750	6290	6695
<b>UPTO 15 CYC</b>	3750	4305	4940	5585	6220	6855	7500	7980
<b>UPTO 10 CYC</b>	4110	4725	5420	6125	6825	7520	8225	8755
10 HT	2515	2890	3315	3745	4175	4600	5030	5355

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.