


# AGRIMAX RT 945

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>380/90 R 50</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | PULVÉRISATEUR / TRACTEUR /<br>OUTILLAGE AGRICOLE   |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 151 A8/B   |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>CODE USA</b> | 94037025 | <b>RC (IN)</b> | 232.3          |
| <b>SW (IN)</b>  | 15.0     | <b>RIM REC</b> | W 12           |
| <b>OD (IN)</b>  | 76.9     | <b>RIM ALT</b> | W 11; W 13     |
| <b>SLR (IN)</b> | 35.7     | <b>ECE</b>     | E4-106R-001487 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 17   | 23   | 29    | 35    | 41    |
|-----------|------|------|------|-------|-------|-------|
| 30        | 4110 | 5320 | 6550 | 7080  | 7600  | -     |
| 25        | 4110 | 5320 | 6550 | 7080  | 7600  | -     |
| 20        | 4410 | 5710 | 7010 | 7580  | 8150  | -     |
| 5         | 6050 | 7420 | 9020 | 10500 | 11070 | 11410 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.