

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 380/70 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZADOR AGRÍCOLA / TRATOR / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 127 D |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 380 | RIM REC | W 12 |
| OD (MM) | 1293 | RIM ALT | W 11; W 13 |
| SLR (MM) | 586 | ECE | E11-106R-005829 |
| RC (MM) | 3883 | SRI | 625 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 965 | 1120 | 1280 | 1435 | 1595 | 1750 |
| 50 | 1015 | 1180 | 1345 | 1510 | 1675 | 1840 |
| 40 | 1060 | 1230 | 1405 | 1575 | 1750 | 1920 |
| 30 | 1110 | 1290 | 1475 | 1655 | 1835 | 2015 |
| 10 LT | 1290 | 1505 | 1715 | 1925 | 2135 | 2345 |
| 10 HT | 1110 | 1290 | 1475 | 1655 | 1835 | 2015 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.