


# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>480/70 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN FÖR FRUKTODLING / LITEN TRAKTOR / TRAKTOR / SKÖRDEMASKIN
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	140 A8 ; 140 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94075393	<b>RC (IN)</b>	166.5
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	55.9	<b>RIM ALT</b>	W 14 L; W 16 L
<b>SLR (IN)</b>	24.8	<b>ECE</b>	E11-106R-009049

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	3040	3530	4030	4520	5020	5520
25	3040	3530	4030	4520	5020	5520
20	3260	3790	4310	4840	5370	5900
5 LT	4070	4730	5410	6070	6730	7390
5 HT	3260	3790	4310	4840	5370	5900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.