


# AGRIMAX V- FLECTO



<b>TIRE SIZE</b>	<b>VF 650/70 R 34 NRO</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94074785	<b>RC (IN)</b>	197.8
<b>SW (IN)</b>	23.7	<b>RIM REC</b>	DW 21 B
<b>OD (IN)</b>	67.1	<b>RIM ALT</b>	DW 20 B
<b>SLR (IN)</b>	29.1	<b>ECE</b>	E11-106R-008813

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	6020	6980	7940	9030	9990	10950	12040
<b>FROM 40 TO 25</b>	6610	7670	8730	9920	10980	12040	13230
20	6750	7810	8900	10120	11190	12270	13490
12	6880	7970	9070	10320	11410	12510	13760
5	7270	8430	9600	10910	12070	13240	14550
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	9260	10740	12210	13890	15370	16840	18520
5 HT	6750	7810	8900	10120	11190	12270	13490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.