


RIDEMAX FL 693 M



| | |
|---------------------|--|
| TIRE SIZE | 650/50 R 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TANKER / TRAILER / IMPLEMENTS |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 163 D ; 160 E |

DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 645 | RIM REC | AG 20.00 |
| OD (MM) | 1222 | ECE | E4-106R-001417 |
| SLR (MM) | 535 | SRI | 575 |
| RC (MM) | 3715 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|
| 70 | 1645 | 1845 | 2295 | 2610 | 3015 | 3420 | 3735 | 4095 | 4500 |
| 65 | 1780 | 2000 | 2490 | 2830 | 3270 | 3705 | 4050 | 4440 | 4875 |
| 50 | 2155 | 2420 | 3010 | 3425 | 3955 | 4485 | 4900 | 5370 | 5900 |
| 40 | 2425 | 2720 | 3385 | 3850 | 4445 | 5040 | 5505 | 6035 | 6630 |
| 25 | 2815 | 3160 | 3930 | 4470 | 5165 | 5860 | 6400 | 7015 | 7705 |
| 10 | 3205 | 3600 | 4480 | 5090 | 5880 | 6670 | 7285 | 7990 | 8775 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.