


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>500/70 R 24 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	164 A8 ; 159 D



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94070244	<b>RC (IN)</b>	155.7
<b>SW (IN)</b>	19.8	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	51.6	<b>RIM ALT</b>	DW 15 L ; DW 18 L
<b>SLR (IN)</b>	23.7	<b>ECE</b>	E11-106R-007547

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	52	58
40	3860	4730	5310	6270	7140	8010	8780	9640
30	4170	5110	5730	6780	7720	8650	9480	10420
25	4410	5400	6060	7160	8160	9150	10030	11020
20	4630	5680	6370	7530	8560	9610	10540	11570

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.