


EARTHMAX SR 22 AS

17.5 R 25

UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	YÜKLEYİCİ / GREYDER
VERSION	CUT RESISTANT COMPOUND
TIRE TYPE	TL

167 B ; 153 A8 ; 182 A2



UNDEFINED IS STANDARD

OD (MM)	1350	TRA CODE	E2/G2/L2
SLR (MM)	595	STAR RATING	★★/★/★★
RC (MM)	4010		
RIM REC	14.00/1.5		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25
50	-	-	-	-	-	-	-	-	4375	4625	4750	5000	5150	5450	-	-	-	-
40	1850	2120	2360	2650	2900	3075	3350	3650	-	-	-	-	-	-	-	-	-	-
10	-	-	-	-	-	-	-	-	-	-	-	-	-	7300	7500	7750	8000	8250

KM/H / BAR	6.50
50	-
40	-
10	8500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.