

# AW 708

<b>TIRE SIZE</b>	500/50 - 17
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	152 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	500	<b>RIM REC</b>	16.00
<b>OD (MM)</b>	945	<b>PR</b>	16
<b>SLR (MM)</b>	416		
<b>RC (MM)</b>	2750		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.20
10 FR	4970
25 FR	4225
30 FR	3975
40 FR	3550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.