

# AT 603

|                           |                                     |
|---------------------------|-------------------------------------|
| <b>TYRE SIZE</b>          | <b>12.5/80 - 18</b>                 |
| <b>UM</b>                 | IS STANDARD                         |
| <b>CONSTRUCTION</b>       | ⊗ BIAS                              |
| <b>MACHINERY</b>          | IMPLEMENT MACHINERY /<br>IMPLEMENTS |
| <b>VERSION</b>            | STANDARD                            |
| <b>TYRE TYPE</b>          | TL                                  |
| <b>LI/SS DRIVE WHEEL</b>  | 135 A8                              |
| <b>LI/SS FREE ROLLING</b> | 148 A8                              |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 308  | <b>RIM REC</b> | W 9             |
| <b>OD (MM)</b>  | 1000 | <b>RIM ALT</b> | 11              |
| <b>SLR (MM)</b> | 448  | <b>ECE</b>     | E11-106R-004351 |
| <b>RC (MM)</b>  | 3027 | <b>PR</b>      | 16              |

## LOAD CAPACITY (KG/TYRE)

| <b>KM/H / BAR</b> | <b>4.90</b> |
|-------------------|-------------|
| 10 FR             | 4410        |
| 25 FR             | 3750        |
| 30 FR             | 3530        |
| 40 FR             | 3150        |
| 10 DW             | 3050        |
| 25 DW             | 2595        |
| 30 DW             | 2440        |
| 40 DW             | 2180        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.