

EARTHMAX SR 31



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 31

EARTHMAX SR 31 is an All Steel radial tyre specially designed for articulated dump trucks and wheel loaders. It provides extraordinary strength and stability, whilst the non-directional rigid block pattern stands for both excellent traction and maneuverability even on muddy ground. EARTHMAX SR 31 also features a special tread compound which is particularly cut-and-heat resistant. The radial casing structure also provides reduced rolling resistance offering significant fuel savings.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø25"	29.5 R 25	TL	L3	**	216 A2	25.00/3.5	-	0	765	1861	818	5555	42	CR
	23.5 R 25	TL	E3/L3	**/*	185 B 195 A2	19.50/2.5	-	200	612	1607	711	4797	34	CR
	26.5 R 25	TL	E3/L3	**/*	193 B 202 A2	22.00/3.0	-	230	689	1742	766	5200	38	CR
	26.5 R 25	TL	L3	**	209 A2	22.00/3.0	-	0	689	1742	766	5200	38	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES				
							
E3/L3	B						
	216 kg						

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 20/09/2026

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
29.5 R 25	TL	E3/L3	**/*	200 B 208 A2	25.00/3.5	-	270	765	1861	818	5555	42	CR
20.5 R 25	TL	E3/L3	**/*	177 B 186 A2	17.00/2.0	--	170	540	1480	663	4449	32	CR

CR: CUT RESISTANT COMPOUND



TECHNOLOGIES			PERFORMANCES				
							
E3/L3	B	216 kg					

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 20/09/2026