



## DATA SHEET

Última  
actualización  
10-07-2026

# TR 135

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>23.1 - 34</b>   |
| <b>UM</b>        | US STANDARD        |
| <b>MACHINERY</b> | TRACTOR / REMOLQUE |
| <b>VERSIÓN</b>   | STANDARD           |
| <b>TIRE TYPE</b> | TT                 |
| <b>LI/SS</b>     | 150 A8             |



### DIMENSIONES US STANDARD

|                   |          |                |                   |
|-------------------|----------|----------------|-------------------|
| <b>CÓDIGO USA</b> | 94034222 | <b>RC (IN)</b> | 209.5             |
| <b>SW (IN)</b>    | 23.0     | <b>RIM REC</b> | DW 20 B ; DW 20 A |
| <b>OD (IN)</b>    | 71.3     | <b>ECE</b>     | E4-106R-002831    |
| <b>SLR (IN)</b>   | 32.8     | <b>PR</b>      | 10                |

### LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>20</b> |
|------------------|-----------|
| 25               | 7400      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.