



US standard



GROWING TOGETHER

# SM 54 M IND-4S



PRODUCT DATA SHEET



Bias



# SM 54 M IND-4S

SM 54 M (L-4S) IND-4S is a modified version of the SM 54 pattern. The flatter tread profile results in a large contact area ensuring a longer tire life-cycle. This tire has been specially designed for empty container handlers and reach stackers in intermodal/logistics applications. SM 54 M features high stability in lift mode as well as a deep and smooth tread design, providing excellent cut resistance.

### Technologies



Deep Tread

### Performance



Cut and Chip Resistance



Durability



Stability

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
							(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 25"	94055791	18.00 - 25	TL	40	-	PORT IND	65.0	20.8	29.5	192.1	74	1023	13.00/2.5	15.00/2.5
Ø 33"	94050208	18.00 - 33	TL	36	-	PORT IND	74.6	21.1	33.1	220.8	75	1158	13.00/2.5	-
	94074914	18.00 - 33	TL	40	-	PORT IND	74.6	21.1	33.1	220.8	75	1223	13.00/2.5	-

PORT IND: Port Industrial



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference