

# FLOTATION 648

<b>TIRE SIZE</b>	<b>800/45 - 26.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	170 A8/167 B
<b>LI/SS FREE ROLLING</b>	183 A8/180 B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94052929	<b>RC (IN)</b>	164.8
<b>SW (IN)</b>	31.5	<b>RIM REC</b>	AG 28.00
<b>OD (IN)</b>	54.8	<b>ECE</b>	E11-106R-004618
<b>SLR (IN)</b>	24.8	<b>PR</b>	20

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	38	39	41
5 FR	25860	26430	27010
10 FR	23280	23790	24300
20 FR	20690	21150	21600
25 FR	18470	18880	19290
30 FR	16620	17000	17640
5 DW	17740	18130	18520
10 DW	15960	16320	16670
20 DW	14190	14510	14810
25 DW	12660	12950	13230
30 DW	11400	11660	12010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.