


# PL 801

<b>TIRE SIZE</b>	<b>5.50 - 15</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ROTORSCHWADER / ERNTEMASCHINE / GABELSTAPLER / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / GABELSTAPLER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94030545	<b>RIM ALT</b>	4.50 E SDC
<b>SW (IN)</b>	6.2	<b>PR</b>	8
<b>OD (IN)</b>	26.4		
<b>RIM REC</b>	4.50 E DT		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	106
<b>15 LOAD WHEEL</b>	4300
<b>15 STEER WHEEL</b>	3185
<b>5 OTHER VEHICLES</b>	4300
<b>15 OTHER VEHICLES</b>	3185
<b>STATIC SIDE LOADER</b>	4805

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.